





## GENERAL SPECIFICATIONS

|                                                   |                                            |
|---------------------------------------------------|--------------------------------------------|
| Category                                          | Sub-category                               |
| <b>Glitter</b>                                    | <b>Glitter</b>                             |
| Finishes                                          | <b>Textured</b>                            |
| <b>Textured</b>                                   | Type of product                            |
|                                                   | <b>PET</b>                                 |
| Width                                             | Length                                     |
| <b>122 cm</b>                                     | <b>30 m</b>                                |
| Adhesive                                          | <b>Acrylic PSA with air release system</b> |
| Warranty                                          | <b>10</b>                                  |
| Stretchable                                       | <b>Not Stretchable</b>                     |
| Resistance to scratch                             | <b>Average</b>                             |
| Pattern direction                                 | <b>-</b>                                   |
| Thickness (average by category)                   | <b>400 µm</b>                              |
| Storage condition (maximum 3 years from delivery) | <b>5° C - 30° C</b>                        |
| Installation method                               | <b>Dry</b>                                 |
| Installation area                                 | <b>Interior</b>                            |
| Installation temperature                          | <b>12° C - 38° C</b>                       |
| Installation method (ABBA - ABAB)                 | <b>ABAB</b>                                |
| Pattern repetition length (cm)                    | <b>-</b>                                   |
| Overlap to match layers (cm)                      | <b>-</b>                                   |
| RAL color                                         | <b>9023</b>                                |



## CERTIFICATIONS

|                                                       |                      |                                                                               |                      |
|-------------------------------------------------------|----------------------|-------------------------------------------------------------------------------|----------------------|
| CE Wallcovering (EN15102)                             | <b>Compliant</b>     | Color fastness to rubbing (ISO 105-X12) - Assessment according to grey scales | <b>Not tested</b>    |
| REACH                                                 | <b>Compliant</b>     |                                                                               |                      |
| Aldehydes after emission (CMR ISO 16000)              | <b>Not tested</b>    | Color fastness to shampooing (ISO 18168)                                      | <b>Not tested</b>    |
| Volatile Organic Compounds Testing (EN16516)          | <b>Not tested</b>    | Color fastness to water (ISO 105-E01)                                         | <b>Not tested</b>    |
| Fire rating (EN13501-1)                               | <b>D-s1,d0</b>       | Liquid absorbency capacity (ISO 9073-6 2000)                                  | <b>Not tested</b>    |
| Wall covering - specification for cork roll (EN13085) | <b>Not required</b>  | Liquid wicking rate (ISO 9073-6 2000)                                         | <b>Not tested</b>    |
| IMO/MED Modul B - E                                   | <b>Not compliant</b> | Dimensional stability (ISO 3759) - 24h at 50° C - 65% humidity                | <b>Not tested</b>    |
| RAIL (ISO 5658 - 2:2006 + A1:2011)                    | <b>Not tested</b>    | Heat and thermal cycle resistance                                             | <b>Tested</b>        |
| Stain resistance (Tchibo)                             | <b>Tested</b>        | Color fastness to light                                                       | <b>Not Tested</b>    |
| Antibacterial properties JIS Z 2081 am. 1 (2012)      | <b>Not tested</b>    | Adhesion Test                                                                 | <b>Tested</b>        |
| Spongeability (EN12956)                               | <b>Not tested</b>    | Moisture resistance                                                           | <b>Not compliant</b> |
| Washability (EN12956)                                 | <b>Not tested</b>    |                                                                               |                      |
| Scrubability (EN12956)                                | <b>Not tested</b>    |                                                                               |                      |

## CARE AND MAINTENANCE

## DURABILITY:

This product offers exceptional resistance to water, dirt, abrasion, UV rays and wear (yellowing, crackling, scaling, delamination).

## MAINTENANCE:

For daily care, use a mild soap or pH-neutral detergent to clean the film's surface. Avoid using products with extremely acidic or basic pH levels, as they can harm the material. When cleaning the film surface, only use soft cloths or sponges to prevent any damage. For stubborn stains, apply hot water (not boiling) to the affected area. If necessary, use a solution of 70% isopropyl alcohol, 30% water for cleaning. However, refrain from using this solution on printed film surfaces. For sanitizing, use only isopropyl alcohol-based products like Isopropyl Alcohol Wipes (not for daily use). Avoid organic-based cleaners like ammonia or polish, as they can damage vinyl. Test any cleaning detergents, bactericides, or virucidal products on a hidden area first to ensure compatibility. For Cork Prestige references, minimal cleaning and care are required due to their natural resistance to dust and dirt. Use a brush with gentle bristles to clean. In case of wet or damp stains, use an absorbent cloth to wipe away the moisture and promptly and thoroughly dry the affected area. These recommendations will maintain the film's appearance and extend its lifespan. Persistent stains may indicate inadequate care, in which case, consider using a patch repair method (not guaranteed but effective and economical) or replacing the entire vinyl.

Non-contractual visuals and data, Cover Styl reserves the right to change the composition of its films at any time. The rendition of the colours and finishes on the computer may vary according to the screen and not give a true representation of the true appearance. We therefore recommend you order a sample on line or contact us so that we can examine the finish that best adapts to your requirements. Due to the slight differences in colour in production runs, we advise you to purchase the amount you require in one go to avoid any difference in appearance in the execution of your Cover Styl project.